

PROFESSIONAL SOUND SYSTEMS



SVP-X Series

The brand new SVP-X Series, a new generation of our SVP, is designed to meet today's most demanding professional applications. Building on the worldwide success of the SVP series, SVP-X is a series of high power, accurate and portable loudspeakers that are designed to deliver high quality sound for the best value possible.

Genuine Wharfedale Pro woofers, high-efficiency compression driver, elliptical Waveguide (EWG™) technology and Protech™ driver protection all ensure that the SVP-X Series stands out as the best value in a professional sound reinforcement loudspeaker.

Reduced in size and weight, the SVP-X enclosure is significantly smaller than the first generation. With its heavy duty components, new ergonomic handle design, integral aluminium stand mount socket and durable carpet finish, the SVP-X will rise to any sound reinforcement challenge.

The SVP-X Series includes a range of full range systems from the SVP-X12 to the SVP-X215 plus the SVP-12M passive floor monitor and SVP-X18B high powered bass reflex subwoofer.

FEATURES

- 2-way trapezoidal reflex systems
- Road tough subwoofer systems
- 1.2 inch (30mm) phenolic diaphragm compression driver
- Low distortion, high power woofers
- 90° x 60° High Frequency Elliptical Wave Guide (EWG)
- High slope crossover with high voltage components
- Auto resetting thermal fuse driver protection
- High power 3 voice coil subwoofer
- Covered in rugged black carpet
- Tear drop shaped handles
- Integrated Stand adapter
- Speakon™ x 2 parallel speaker inputs



www.wharfedalepro.com

PROFESSIONAL SOUND SYSTEMS

SVP-X Series



SPECIFICATIONS



Model	SVP-X12	SVP-X12M	SVP-X15	SVP-X215	SVP-X18B
Loudspeaker Type:	12" 2-way	12" 2-way Monitor	15" 2-way	2 x 15" 2-way	18" subwoofer
Frequency Response (+/-3dB):	50-20kHz	50-20kHz	45-20kHz	40-20kHz	40-250Hz
Sensitivity (1W@1M):	97dB	97dB	98dB	101dB	99dB
Peak SPL:	124.5dB	124.5dB	126dB	129.5dB	129.5dB
HF Coverage (H x V):	90° x 60°	90° x 60°	90° x 60°	90° x 60°	-
System Impedance:	8 ohm	8 ohm	8 ohm	4 ohm	8 ohm
POWER (WATTS)					
Continuous/ Music/ Peak	150/300/600W	150/300/600W	200/400/800W	250/ 500/ 1000W	300/ 600/ 1200W
LF DRIVER					
Size	304.8mm/12 "	304.8mm/12 "	381mm/ 15 "	381mm/ 15 "	457.2mm/18 "
Coil Size	50.8mm/ 2.0 "	50.8mm/ 2.0 "	50.8mm/ 2.0 "	38.1mm/ 1.5 "	76.2mm / 3.0 "
HF DRIVER/ HORN					
Driver Type:	Compression Driver	Compression Driver	Compression Driver	Compression Driver	-
Coil Size	25mm/1 "	25mm/1 "	25mm/1 "	25mm/1 "	-
Exit Size	30mm/1.2 "	30mm/1.2 "	30mm/1.2 "	30mm/1.2 "	-
Diaphragm Material:	Phenolic	Phenolic	Phenolic	Phenolic	-
HF Driver Protection:	PTC	PTC	PTC	PTC	-
Horn Type:	Elliptical	Elliptical	Elliptical	Elliptical	-
Throat Size:	25.4mm/1 "	25.4mm/1 "	25.4mm/1 "	25.4mm/1 "	-
CROSSOVER					
Frequency	2-way 3.2KHz	2-way 3.2KHz	2-way 3.2KHz	2-way 3.2KHz	-
ENCLOSURE					
Shape/ Material:	Trapezoidal	40°/50° Monitor	Trapezoidal	Trapezoidal	Rectangular
Handles	2	1	2	2	2
INPUT PANEL					
Input Connectors:	2 x Speakon™	2 x Speakon™	2 x Speakon™	2 x Speakon™	2 x Speakon™
Hi pass output	-	-	-	-	1 x Speakon™
Dimensions(mm/inch)					
H	566.5/21.9"	554/21.8"	650/525.6"	1063/41.9"	652.5/25.7"
W	398(232.2)/15.7(9.2)"	398/15.7"	457(280.5)/18.0(11.0)"	492(300) /19.4(11.8)"	512/20.2"
D	332/13.1"	389.5/14.6"	340/13.4"	365/14.4"	450/17.7"
Weight:	14.3kg / 31.5 lbs	14.63kg / 32.1 lbs	17.5kg / 38.5 lbs	27kg / 59.4 lbs	30.8kg / 67.8 lbs

Wharfedale Professional
 IAG House, Sovereign Court, Ermine Business Park, Huntingdon, Cambs, PE29 6XU, England
www.wharfedalepro.com

The information in this brochure is subject to change without notice. All rights reserved ©2008 Wharfedale Pro. Wharfedale Pro is a member of the International Audio Group.